

Product data sheet

Atlanta

0530/FR-408

duraplus®



SecuSignal®

Secustik®

VarioFit®



| | |
|--------------------|-------------------------------|
| Article number | 10804184 |
| EAN-Code | 4012789696554 |
| Country of origin | Germany |
| CN-Code | 83024150 |
| Diameter lug | 10 mm |
| Spindle size | 7 mm |
| Spindle length | 32-42 mm |
| Spindle length | 7 mm / projecting 32-42 mm |
| Stop position in ° | 90° |
| Screws | M5x55 mm + M5x60 mm |
| Finish | F1 aluminium silver effect |
| Range | Core Product Range |
| Packing unit | 1 |
| Outer carton | 10 |

HOPPE eHandle **SecuSignal®** for windows – aluminium turn/tilt window handle with **Secustik®** and **VarioFit®**:

- Stop-in position: 90°
- Cover: full cover cap
- Base: nylon, supporting lugs
- Spindle: HOPPE solid spindle, adjustable length of 10 mm, smooth adjustment thanks to the pressure spring integrated in the handle neck
- Fixing: concealed, M5 thread screws

Technical Data:

- Storage temperature -20 °C to +65 °C, Operating temperature +5 °C to 40 °C
- Max. relative air humidity: 80%, non-condensing
- Wireless protocol: EnOcean EEP F6-10-00
- Wireless frequency: 868 MHz
- Transmission rate: 120 kbps +/- 5%
- Information transmitted: handle position (open/tilted/closed)
- Transmission power: max. 10mW EIRP
- Wireless range: max. 30 m according to EnOcean specification, depending on the building condition
- Power supply: battery-free, by Energy Harvesting

