

Product data sheet

Hamburg

099KH/300LMSG-L-D/NLFSGL/1700

duraplus®



Quick-Fit



Article number	11747730
EAN-Code	4012789881660
Country of origin	Germany
CN-Code	83024150
Grade	3
Corrosion resistance	4
Door thickness	58-67 mm
Spindle size	8 mm
Spindle length	
(Key)Hole size	Euro profile cylinder
Key hole distance	92 mm
Finish	F9 aluminium steel effect
Range	Core Product Range
Packing unit	5
Outer carton	30

HOPPE aluminium handle set on narrow backplate for French doors:

- Tested to **EN 1026** (air permeability) and **EN 1027** (water tightness); rated according to **EN 12207: A*4** (air permeability) and **EN 12208: E*5A** (water tightness); suitable for entrance doors that comply with **RT 2012** (French Energy Efficiency Directive) and **NF 220, NF 297** and **NF 412** standards
- Bearing: handle with short neck on the outside, door handle on the inside, both loose, maintenance-free slide bearing
- Connection: **HOPPE Quick-Fit connection** with HOPPE solid spindle (spindle - receiver components)
- Backplates: supporting lugs, sealing liner on the outside
- Fixing: visible inside, bolt-through, M4 thread screws
- Special feature: Exterior backplate with sealing liner for energy efficiency and protection against rain and condensed water

