

Product data sheet

Toulon

0737/FR-409

duraplus®



SecuSignal®

Secustik®

VarioFit®



Article number	11750583
EAN-Code	4012789884883
Country of origin	Germany
CN-Code	83024150
Diameter lug	10 mm
Spindle size	7 mm
Spindle length	32-42 mm
Spindle length	7 mm / projecting 32-42 mm
Stop position in °	90°
Screws	M5x55 mm + M5x60 mm
Finish	F9016M matt traffic white
Range	Core Product Range
Packing unit	1
Outer carton	10

HOPPE eHandle **SecuSignal®** for windows – aluminium turn/tilt window handle with **Secustik®** and **VarioFit®**:

- Stop-in position: 90°
- Cover: full cover cap
- Base: nylon, supporting lugs
- Spindle: HOPPE solid spindle, adjustable length of 10 mm, smooth adjustment thanks to the pressure spring integrated in the handle neck
- Fixing: concealed, M5 thread screws

Technical Data:

- Storage temperature -20 °C to +65 °C, Operating temperature +5 °C to 40 °C
- Max. relative air humidity: 80%, non-condensing
- Wireless protocol: EnOcean EEP F6-10-00
- Wireless frequency: 868 MHz
- Transmission rate: 120 kbps +/- 5%
- Information transmitted: handle position (open/tilted/closed)
- Transmission power: max. 10mW EIRP
- Wireless range: max. 30 m according to EnOcean specification, depending on the building condition
- Power supply: battery-free, by Energy Harvesting

