

Product data sheet

duraplus[®]

E5061BC



Article number	11963943
EAN-Code	4012789077223
Country of origin	Germany
CN-Code	83024110
Diameter/cross section	35 mm
Length	1600 mm
Fixing distance	1200 mm
Electrical connector	universal connection (4 open cable ends with cable end sleeve)
Finish	F69 satin stainless steel
Range	Core Product Range
Packing unit	1
Outer carton	1

HOPPE eHandle FingerScan for doors – stainless steel bar-shaped pull handle, with finger scanner:

- Supports: round, straight
- Fixing: concealed, pull handle fixing system no. 11

Technical Data:

- Operating temperature: -25 °C to +70 °C
- Protection class: eHandle for doors IP 44, controller IP 30
- Finger scanner: capacitive fingerprint sensor
- False acceptance rate (FAR): 1:10,000,000
- Memory: Number of users in basic version 20 (80 fingers) max.; more users (fingers) as an optional extra
- Operating voltage of motorised lock: 10-30V DC
- Power consumption: max. approx. 1,3W
- Current-carrying capacity of switch contact: max. 30V/1A
- Switching time: 1s min./20s max.
- Configuration/Control: ekey bionyx App
- Product can only be used with the ekey bionyx app! (The app must be downloaded separately)

Included in scope of delivery:

- ekey-dLine control unit (mounting plate to be ordered separately)
- ekey-dLine finger scanner control unit cable

