

Product data sheet

Amsterdam

E86GBC/42H/42NSB-ZA/42HS/1400

duraplus®



Quick-Fit



Article number	11964510
EAN-Code	4012789081244
Country of origin	Germany
CN-Code	83024110
Door thickness	67-77 mm
Spindle size	8 mm
Spindle length	
(Key)Hole size	Euro profile cylinder
Electrical connector	universal connection (4 open cable ends with cable end sleeve)
Finish	F69 satin stainless steel
Range	Core Product Range
Packing unit	1
Outer carton	5

HOPPE eHandle FingerScan for doors – stainless steel security knob/handle set on rose with cylinder cover and finger scanner for entrance doors:

- Tested to **DIN 18257 ES1 (SK2)**
- Bearing: fixed cranked knob (pad) on the outside, suitable for right and left hand; loose door handle on the inside, non-handed spring cassette, maintenance-free slide bearing
- Connection: **HOPPE Quick-Fit connection** with HOPPE solid spindle (receiver component)
- Cylinder cover: hardened steel, for cylinder projection 10-18 mm
- Base: steel, supporting lugs
- Fixing: concealed, bolt-through, M5 thread screws

Technical Data:

- Operating temperature: -25 °C to +70 °C
- Protection class: eHandle for doors IP 44, controller IP 30
- Finger scanner: capacitive fingerprint sensor
- False acceptance rate (FAR): 1:10,000,000
- Memory: Number of users in basic version 20 (80 fingers) max.; more users (fingers) as an optional extra
- Operating voltage of motorised lock: 10-30V DC
- Power consumption: max. approx. 1,3W
- Current-carrying capacity of switch contact: max. 30V/1A
- Switching time: 1s min./20s max.
- Configuration/Control: ekey bionyx App
- Product can only be used with the ekey bionyx app! (The app must be downloaded separately)

Included in scope of delivery:

- ekey-dLine control unit (mounting plate to be ordered separately)
- ekey-dLine finger scanner control unit cable

