

Product data sheet


Premier

AR915-ESC



ARRONE mortice apartment lock case:

- Function: Latch bolt and deadbolt with escape operation for half set lever handle sets
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: ABB010, UKCA Marked: AG7668
 - **BS EN 179**: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
 - **BS EN 179**: 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530,CE DOP: HUK0035 and HUK0012, UKCA DOP: HUK0035-UK and HUK0012-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR915 series lock case has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
 responsibility for any locks purchased and fitted without sufficient intumescent protection.



| Article number | 50001486 |
|-------------------|-----------------------|
| Product ref. | AR915-ESC-R-60- |
| | PSS |
| EAN-Code | 5051358076426 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Operation | Half Lever Set |
| Follower | 8 mm |
| Backset | 60 mm, pierced for |
| | furniture and es- |
| | cutcheons at 38 mm |
| | centres |
| (Key)Hole size | Euro profile cylinder |
| Key hole distance | 72 mm |
| Door type | wooden door |
| Fixings | Timber door |
| Corner | radius corners |
| Shape | radiused |
| Finish | polished stainless |
| | steel |
| Face plate finish | F68 polished stain- |
| | less steel |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 25 |