

Premier

## Product data sheet


## AR912

6

.



- Function: Deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: AG0068, UKCA Marked: AG7669
- Certifire approved: CF530, CE DOP: HUK0008, UKCA DOP: HUK0008-UK - **BS EN 12209**: 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 0 | 0
- Testing: BS EN 1634-1. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of BS 8300 and ADM for locks
- \* The AR912 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.





HOPPE (UK) · Ltd Gailey Park · Gravelly Way · Standeford · Wolverhampton WV10 7GW

Tel. 01902 484 400 · Tel. Sales Direct: 01902 484 410/20 · Fax 01902 484 406 · Fax Sales Direct: 01902 484 417/27 · info.uk@hoppe.com · www.hoppe.com