

## Product data sheet

## Premier

AR6509



ARRONE overhead door closing device:

- Power size: 2 to 5 adjustable by spring tension
- Function: Closing, latching, backcheck, delayed action
- Cover: Box cover
- Maximum door width: 1,250 mm
- Maximum door weight: 100 kg
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
  - Door mount pull side: 4 | 8 | 5/2 | 1\* | 1 | 3
  - Transom mount push side: 3 | 8 | 5/2 | 1\* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD5285, UKCA Marked: AD7690
- Certifire approved: CF5430, CE DOP: HUK0066, UKCA DOP: HUK0066

Article number	50008444
Product ref.	AR6509B-BX-SE
EAN-Code	5051358084544
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1250 mm
Maximum door weight	100 kg
Arm Application	door mount pull, transom mount push
Mechanism function	Backcheck, delayed action, spring adjustment, closing/latching speed
Mechanism type	cam action
Fixings	Timber door
Slide track application	door mount pull, transom mount push
Shape	Box
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	256.5x60x48mm; centres 112x45mm
Arm type	Surface slide arm
Finish	Silver Enamel
Finish of the cover	Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	4

