

Product data sheet

Perform

AR9500



ARRONE door closing device:

- Power size: 2 to 6 by spring adjustment
- Function: Closing, latching, backcheck
- Cover: Slide cover
- Maximum door width: 1,400 mm (Fig 1), 1,250 mm (Fig 6)
- Maximum door weight: 120 kg (Fig 1), 100 kg (Fig 6)
- Arm application: Fig 1, Fig 6
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull (Fig 1): 4 | 8 | 6/2 | 1* | 1 | 3
 - Door mount push (Fig 6): 4 | 8 | 5/3 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minute Timber fire doors and 240 minutes on fully insulated Steel fire doors
- CE Marked: AD0162, DOP: HUK0029
- Certifire Approved: CF295

Article number	50013609
Product ref.	AR9500-L-SSS/SSS-A2-O
EAN-Code	5051358004504
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1400 mm
Maximum door weight	120 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Backcheck, spring adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Slimline
Power size	2 to 6
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	256.5x60x48.2 mm; 118.5x218.5x45 mm
Arm type	Scissor arm, detachable joint, flat form, adjustable
Finish	Satin Stainless Steel
Finish of the cover	Satin Stainless Steel
Arm finish	Satin Stainless Steel
Range	ARRONE Range
Packing unit	4
Outer carton	50

