

Product data sheet

Plus

AR9500SD



ARRONE overhead door closer:

- Power size: 2 to 6 adjustable by spring tension
- Function: Closing speed, latching speed, back check
- Cover: Slide cover
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Maximum door width: 1400 mm (Fig 1 & Fig 61), 1100 mm (Fig 6)
- Maximum door weight: 120 kg (Fig 1 & Fig 61), 100 kg (Fig 6)
- Testing: **BS EN 1154:1997**
 Door mount pull (Fig 1): 4 | 8 | 6/2 | 1* | 1 | 3
 Door mount push (Fig 6): 3 | 8 | 5/2 | 1* | 1 | 3
 Transom mount (Fig 61): 4 | 8 | 6/2 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on up to 240 minute Steel un-insulated fire doors.
- CE Marked: AD5473, UKCA Marked: AD7693

Article number	50017809
Product ref.	AR9500SD-SE
EAN-Code	5051358010482
Country of origin	China
CN-Code	83026000
Door type	Metal door
Maximum door width	1400 mm
Maximum door weight	120 kg
Arm Application	figure 1 and 6
Mechanism function	Backcheck, spring adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Metal door
Shape	Trim Plate
Power size	2 to 6
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	275x63x46 mm; centres 50x50x43 mm
Arm type	scissor arm, adjustable
Finish	Silver Enamel
Finish of the cover	Silver Enamel
Arm finish	Silver Enamel
Range	ARRONE Range
Packing unit	0
Outer carton	0

