

Product data sheet

Perform

AR6800



ARRONE door closing device:

- Power size: 2 to 4 adjustable by template
- Function: Closing, latching
- Cover: no cover
- Maximum door width: 1,100 mm (Fig 1), 950 mm (Fig 6 and Fig 61)
- Maximum door weight: 80 kg (Fig 1), 60 kg (Fig 6 and Fig 61)
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull (Fig 1), transom mount push (Fig 61): 3 | 8 | 4/2 | 1* | 1 | 3
 - Door mount push (Fig 6): 3 | 8 | 3 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD0095, UKCA Marked: AD7696
- Certifire approved: CF603, CE DOP: HUK0025, UKCA DOP: HUK0025-UK

Article number	87105960
Product ref.	AR6800-SE
EAN-Code	5051358027213
Country of origin	Taiwan
CN-Code	83026000
Type	mechanism only
Door type	wooden door
Maximum door width	1100 mm
Maximum door weight	80 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Template adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	
Power size	2 to 4
Opening Angle	max. 105° opening
Mechanism dimensions and fixing centres	219x53.4x45 mm; centres 202x19 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	Silver Enamel
Finish of the cover	
Arm finish	Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	8

