

Product data sheet


Premier

AR910



ARRONE mortice sashlock case:

- Function: Latch bolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: AG0067, UKCA Marked: AG7668
 - **BS EN 12209**: 3 | X | 8 | 1* | 0 | G | 4 | B | A | 3 | 0
- Certifire approved: CF530, CE DOP: HUK0007, UKCA DOP: HUK007-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR910 series lock case has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
 responsibility for any locks purchased and fitted without sufficient intumescent protection.



Article number	87107857
Product ref.	AR910-R-60-PSS
EAN-Code	5051358034358
Country of origin	Portugal
CN-Code	83014019
Operation	Lever/Lever Handle Set
Follower	8 mm
Backset	60 mm, pierced for
	furniture and es-
	cutcheons at 38 mm
	centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Keying	
Corner	radius corners
Shape	radiused
Finish	polished stainless
	steel
Face plate finish	F68 polished stain-
	less steel
Range	ARRONE Range
Packing unit	1
Packing unit Outer carton	1 25