

Product data sheet

AR8805/AR8806

Product ref.AR8806-SEEAN-Code5051358067783Country of originChinaCN-Code83024110Spindle size8 mmSpindle lengthSpindle lengthNumber of pinsFinining and KeyingSpindle size8x90 mmFinishSilver EnamelCylinder finishSilver EnamelPacking unit1Outer carton12		Article number	87138402
Country of originChinaCN-Code83024110Spindle size8 mmSpindle length-Number of pins-Pinning and Keying-Spindle size8x90 mmFinishSilver EnamelCylinder finish-RangeARRONE RangePacking unit1		Product ref.	AR8806-SE
CN-Code83024110Spindle size8 mmSpindle length-Number of pins-Pinning and Keying-Spindle size8x90 mmFinishSilver EnamelCylinder finish-RangeARRONE RangePacking unit1		EAN-Code	5051358067783
Spindle size8 mmSpindle lengthVerticeNumber of pinsPinning and KeyingSpindle size8x90 mmSpindle sizeSilver EnamelCylinder finishSilver EnamelRangeARRONE RangePacking unit1		Country of origin	China
Spindle length Number of pins Pinning and Keying Spindle size 8x90 mm Finish Silver Enamel Cylinder finish Range ARRONE Range Packing unit 1		CN-Code	83024110
Number of pinsPinning and KeyingSpindle size8x90 mmFinishSilver EnamelCylinder finishSilver EnamelRangeARRONE RangePacking unit1		Spindle size	8 mm
Pinning and KeyingSpindle size8x90 mmFinishSilver EnamelCylinder finishRangeRangeARRONE RangePacking unit1		Spindle length	
Spindle size8x90 mmFinishSilver EnamelCylinder finishRangeRangeARRONE RangePacking unit1		Number of pins	
Finish Silver Enamel Cylinder finish Range ARRONE Range Packing unit 1		Pinning and Keying	
Cylinder finishRangeARRONE RangePacking unit1		Spindle size	8x90 mm
RangeARRONE RangePacking unit1		Finish	Silver Enamel
Packing unit 1		Cylinder finish	
		Range	ARRONE Range
Outer carton 12		Packing unit	1
		Outer carton	12

ARRONE lever operated outside access device:

- Function: Lever and key operation
- Body material: Stainless Steel
- Lever material: Stainless Steel
- Maximum door weight: 200 kg
- Options: Device with cylinder (AR8805)
- Testing: Included as part of both single and double door sets in accordance with the requirements of **BS EN 1125: 2008** and **BS EN 179:2008**, **BS EN 1634** Part 1: Assessed for use on 30 and 60 minute timber fire doors and 240 minute steel doors
- Included as an accessory on CE certificate AAA005, ABB015, UKCA certificate UK-AAA7651 and UK-ABB7654
- Included as an accessory on Certifire certificate CF810 and DoP's HUK0022, HUK0023, HUK0022-UK, HUK0023-UK



