

Product data sheet


Perform

AR6800



ARRONE door closing device:

- Power size: 2 to 4 adjustable by template
- Function: Closing, latching
- Cover: no cover
- Maximum door width: 1,100 mm (Fig 1), 950 mm (Fig 6 and Fig 61)
- Maximum door weight: 80 kg (Fig 1), 60 kg (Fig 6 and Fig 61)
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull (Fig 1), transom mount push (Fig 61): 3 | 8 | 4/2 | 1* | 1 | 3
 - Door mount push (Fig 6): 3 | 8 | 3 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD0095, UKCA Marked: AD7696
- Certifire approved: CF603, CE DOP: HUK0025, UKCA DOP: HUK0025-UK



Article number	89001129
Product ref.	AR6800-BLK
EAN-Code	5051358004481
Country of origin	Taiwan
CN-Code	83026000
Type	mechanism only
Door type	wooden door
Maximum door width	1100 mm
Maximum door weight	80 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Template adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	
Power size	2 to 4
Opening Angle	max. 105° opening
Mechanism dimensions and fixing centres	219x53.4x45 mm; centres 202x19 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	RAL 9005 jet black
Finish of the cover	
Arm finish	RAL 9005 jet black
Range	ARRONE Range
Packing unit	1
Outer carton	8